

CUE FOUR



CUE FOUR

3-way high output ultra low profile stage monitor

- 3-way coherent point source technology
 - Double 8" and 1.4" coax driver
 - Asymmetrical vertical coverage 55°+ 40°
 - Outstanding audio quality
 - Ultra low feedback
 - Ultra low profile design
 - Integrated hardware for increased dispersion
 - Mechanically durable
 - Discrete cable connection
 - Passive or bi-amp operation
 - Light weight
- System components: RC20 Rack, DNC260, C10, SC4

The cabinet contains double 8" high power neodymium woofers and a 1.4" coaxial compression driver loaded by an asymmetrical 60° x 55°+40° elliptical waveguide.

The CUE FOUR may be the smallest in the family, but don't let that fool you; once again the CUE FOUR has all the inherent technologies to be found in the series in a smaller footprint. This reduction in physical size and weight makes the CUE FOUR particularly useful in applications where restrictions in placement play their part. This is a big, little monitor, delivers the same high quality audio reproduction and coherency as the CUE ONE and the CUE TWO with the added advantage of being small, low profile and light weight. The CUE FOUR has wall mounting accessories to assist placement in specific applications such; TV studios, Houses of Worship and orchestras.

ACCESSORIES

A4HC	Horizontal U-bracket for CUE FOUR
A4WM	Wall mount bracket for CUE FOUR
FC4CUE	Flight case for 4x CUE FOUR
CFA	Flying Adapter for CUE-Series
CSF	Stand fitting for CUE-Series

TECHNICAL SPECIFICATIONS CUE FOUR

Type:	3-way high output stage monitor
Application:	Stage monitor
Frequency response:	54 Hz - 21 kHz (-3 dB)
Power handling AES:	500 W
Peak Power:	2000 W
Sensitivity:*	104 dB
Max. SPL peak:	137 dB
Dispersion:	
Horizontal:	60°
Vertical:	55° + 40°
Components:	
Low frequency:	2 x 8" neodymium woofers, 2" (52 mm) voice coil, 250 W (AES) each
High frequency:	1.4" neodymium coaxial driver 3.5" (90 mm) + 1.75" (44.4 mm) voice coil, 150 W + 80 W
Crossover:	750 Hz passive or bi-amp (internal connector), 6.3 kHz passive
Nominal impedance:	8 Ohm
Input connectors:	2x Neutrik™ NL4MP
Enclosure material:	15 / 18 mm plywood
Finish:	Textured black paint
Dimensions:	545 x 450 x 272 mm
Net weight:	19 kg
Weatherproof version:	Optional

* Half-space loading