

D5-Ceiling

D5-Ceiling

2-way passive installation system



- Ultra compact 2-way coaxial system
 - Coda Audio 5" / 1" coaxial loudspeaker
 - Attractive solid aluminum design
 - Single point source system providing coherent wave front
 - Superb quality sound
 - Impedance 16 Ohm for easy daisy chaining
- System components: DNC260, C-Series Amplifiers, PW112, PW12A

TECHNICAL SPECIFICATIONS D5-Ceiling

Type:	2-way coaxial ultra compact
Application:	Superior quality short throw
Frequency response:	90 Hz – 30 kHz (-3 dB)
Power handling AES:	125 W
Program power:	250 W
Peak power:	500 W
Sensitivity:	91 dB
Max. SPL peak:	117 dB
Dispersion:	90° conical
Components:	
Low frequency:	5" Woofer, 1.5" (38 mm) voice coil, 120 W
High frequency:	1" coaxially mounted driver, 1.75" (44.4 mm) voice coil, 80 W
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ω
100 V version (optional):	100 VA
Input connectors:	2 x Neutrik™ NL4MP
Enclosure material:	Solid aluminum
Finish:	Metal (all RAL-colours optional available)
Weatherproof version:	Optional
Flying hardware:	M8 Thread
Dimensions (ØxD):	170 x193 mm, ceiling cutout Ø160 mm
Net weight:	4 kg

The Coda D5-Ceiling is a passive 2-way 5" / 1" coaxial loudspeaker system designed without compromise to provide a true one point source in an ultra compact package.

The cabinet contains a high power 5" woofer and a coaxially mounted driver with 44.4 mm voice coil. The advanced design aligns the acoustical centres of the transducers to produce a single point source. This unique loudspeaker technology provides a coherent wave front without hot spots. Precise directivity of 90° conical ensures uniform coverage with perfect time alignment between the components.

Applications include conference, restaurants, pubs, shopping centres, clubs, convention centres, houses of worship and airports.