

K4

K5

K4



2-way compact full range system

- Ultra compact 2-way versatile full range system
- Coda Audio 5" ultra low distortion woofer
- Elliptical waveguide for precise directivity and less distortion
- Superb sound quality
- M6 Flying points
- Improved transient response

K5



2-way compact full range system

- Ultra compact 2-way full range system
- Coda Audio Double 5" ultra low distortion woofer
- Elliptical waveguide for precise directivity and less distortion
- Superb sound quality
- M6 flying points
- Improved transient response

■ System components K4 / K5: DNC260, C-Series Amplifiers, PW112

The Coda Audio K4 is an ultra compact versatile, full range, 2-way loudspeaker system that features a 5" ultra low distortion low frequency driver; the 1" compression driver is coupled to a rotatable 90° x 60° elliptical waveguide. The K4 incorporates a multi design enclosure enabling it to be used horizontally, vertically or as a floor monitor. The addition of flying hardware as standard together with the ability to rotate the elliptical waveguide allows multipurpose applications including conferences, corporate events, PA-systems and houses of worship.

The Coda Audio K5 is an ultra compact full range 2-way loudspeaker system that features double 5" ultra low distortion cone drivers and a 1" compression driver coupled to a rotatable 90° x 60° elliptical waveguide. The addition of M6 flying points as a standard together with the ability to rotate the elliptical waveguide allows multipurpose applications including conferences, corporate events, PA-systems and houses of worship.

ACCESSORIES

CU4V Vertical U-Bracket for K4 A68620 Truss Clamp for K4
195/8 Stand fitting for K4

ACCESSORIES

CU52V Vertical U-Bracket for K5 A68620 Truss Clamp for K5
195/8 Stand fitting for K5

TECHNICAL SPECIFICATIONS K4

Type:	2-way full range multi design
Application:	Superior quality short throw
Frequency response:	80 Hz – 30 kHz (-3 dB)
Power handling AES:	125 W
Program power:	250 W
Peak power:	500 W
Sensitivity:	92 dB
Max. SPL peak:	118 dB
Dispersion:	90° x 60°
Components:	
Low frequency:	5" / 1.5" voice coil ultra low distortion woofer
High frequency:	1" / 1.5" voice coil compression driver
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ohm
Input connectors:	2 x Neutrik™ NL4MP
Enclosure material:	12 mm Baltic birch
Finish:	Textured black paint
Flying Hardware:	8 x M6 threaded points
Dimensions:	160 x 330 x 184 mm
Net weight:	5.45 kg

TECHNICAL SPECIFICATIONS K5

Type:	2-way full range
Application:	Superior quality short throw
Frequency response:	80 Hz – 30 kHz (-3 dB)
Power handling AES:	250 W
Program power:	500 W
Peak power:	1000 W
Sensitivity:	94 dB
Max. SPL peak:	124 dB
Dispersion:	90° x 60°
Components:	
Low frequency:	2 x 5" / 1.5" voice coil ultra low distortion woofers
High frequency:	1" / 1.5" voice coil compression driver
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ohm
Input connectors:	2 x Neutrik™ NL4MP
Enclosure material:	12 / 15 mm Baltic birch
Finish:	Textured black paint
Flying hardware:	6 x M6 threaded points
Dimensions:	160 x 480 x 184 mm
Net weight:	7 kg

